PF	Product Fiche according to (EU) No 65/2014				
S	Supplier's name or trade mark Model identifier Annual Energy Consumption	ALLENZI Rustica 90			
М					
		AEC hood	124.9	kWh/a	
	Energy Efficiency Class	EEI class	D		
	Fluid Dynamic Efficiency	FDE hood	14.9	%	
	Fluid Dynamic Efficiency class	FDE class	D		
	Light Efficiency	LE hood	14.0	lux/W	
	Lighting Efficiency Class	LE class	D		
	Grease Filtering Efficiency	GFE hood	80.7	%	
	Grease Filtering Efficiency class	GFE class	С		
	Minimum Air Flow in normal use	Q min	340	m³/h	
	Maximum Air Flow in normal use	Q max	629	m³/h	
	Air Flow at intensive/boost setting	Q boost	1	m³/h	
	A-weighted Sound Power Emission at minimum speed	SPE min	50	dB(A) re 1pW	
	A-weighted Sound Power Emission at maximum speed	SPE max	61	dB(A) re 1pW	
	A-weighted Sound Power Emission at intensive or boost speed	SPE boost	1	dB(A) re 1pW	
	Power consumption off mode	Ро	0.00	W	
	Power consumption in standby mode	Ps	0.00	W	

Additional Information according to (EU) No 66/2014				
Time increase factor	f	1.5		
Energy Efficiency Index	EEI hood	89.5	%	
Measured air flow rate at best efficiency point	Q bep	383.0	m³/h	
Measured air pressure at best efficiency point	P bep	306	Pa	
Maximum air flow	Q max	629	m³/h	
Measured electric power input at best efficiency point	W bep	219.0	W	
Nominal power of the lighting system	WL	6.8	W	
Average illumination of the lighting system on the cooking surface	E middle	92	lux	